



## PA AMP03VR

30W AMPLIFIER. AMP03VR was specifically designed to deliver announcements and/or music programs through P A systems It can be powered both from a standard AC mains network or by 12 V DC, therefore it is particularly useful for audio distribution on board vehicles.



### Overview

---

AMP03VR was specifically designed to deliver announcements and/or music programs through P.A. systems. It can be powered both from a standard AC mains network or by 12 V DC, therefore it is particularly useful for audio distribution on board vehicles.

#### MAIN FEATURES:

- MP3 file recorder/player module
- Two MIC inputs
- One PHONO/AUX input with selectable sensitivity
- LED power indicator
- Master Volume
- MIC1 Volume Control
- MIC2 Volume Control
- AUX Volume Control
- Low and High Tone Controls
- A screw for ground wiring
- Four outputs: three constant voltage outputs (100 V/70 V/25 V) and one constant impedance output (4 W)
- MIC1 Input Priority Function
- Optional Vehicle Mounting Kit with fixing bracket for the amplifier and power cable with fuse
- Power supply: 220 V AC / 117 V AC 50-60 Hz ; 12 V DC



## Technical Specifications

---

- RMS Output Power: AC 30 W – DC 25 W
- Constant Voltage Output: 100 V / 70 V / 25 V
- Constant Impedance Output: 4 Ohm
- Connettori d'Ingresso: MIC1, MIC2: unbalanced 6.3mm jack (30 – 600 ⓧ)
- AUX /PHONE: RCA 10 kⓧ
- Output connectors: 4 Ohm on screw terminal - 25 V/70V/100V on screw terminal
- Frequency Response: 80 Hz – 18 kHz
- THD: < 1%
- Signal-to-noise ratio: MIC1, MIC2: ≥65 dB
- AUX : ≥75 dB
- PHONE: ≥55 dB
- Input Sensitivity: MIC1, MIC2: -50 dBV @ 1 kHz - AUX: -20 dBV @ 1 kHz - PHONE: -50 dBV @ 1 kHz
- Power Supply: 220 V AC – 117 V AC 50/60 Hz - 12 V DC 5 A
- Dimensions (LxHxP): 280x190x75 mm
- Weight: 4,5Kg

## Related Products

---



PA ACDT180 PA ACDT90 PA AMP03

---

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarks are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

For service, support, or more information contact:  
Proel S.p.A.  
Via alla Ruenia 37/43  
CAP 64027 - Sant'Omero (TE) ITALY

**PROEL** 