


PA CO4006

2-way HF column speaker



Overview

2-way HF column speaker, easy to install, fitted with an internal transformer, metal protection grille and aluminium body, which makes it a very resistant appliance from a mechanical point of view. Particularly suitable for acoustically demanding environments, where thanks to its special design it ensures high sound directivity.

Technical Specifications

Model CO4006 Type Column Speaker Speakers W: $6 \times 2''$ T: 1'' Power taps @ 100V 40/20/10W Frequency response 180Hz - 18KHz SPL(1W/m) 91 dB SPL MAX (Pmax @ 1m) 107 dB Coverage Angle 1KHz/4KHz (-6dB) V:40°/30° H:170°/140° Construction materials Aluminium Colour White (RAL 9010) Dimensions (W x H x D) 78 x 505 x 66 mm Weight 2.2Kg Fixing system Bracket

Related Products



Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarke are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

For service, support, or more information contact: Proel S.p.A. Via alla Ruenia 37/43 CAP 64027 - Sant'Omero (TE) ITALY

